

A sleek, black Culligan Purity Prime water cooler. The machine has a modern, minimalist design with a large, circular touch-screen interface on the right side. The screen displays a blue star icon in the center, surrounded by smaller icons for different water settings. The Culligan logo is visible on the top left of the machine's body. The background is a light gray gradient.

Culligan

Culligan Purity™

Prime

Culligan Purity Prime redefines high-performance hydration. Engineered for the largest teams and busiest spaces, it uses our most advanced technologies to deliver clean, safe, great-tasting water with consistency and ease. Choose from six water modes to satisfy every preference: cold, ambient, light sparkling, extra sparkling, hot and extra hot.

- ✓ Advanced multi-stage filtration
- ✓ Firewall® UVC technology
- ✓ C-Sense smart monitoring technology
- ✓ Up to 60 users

Mains-fed water cooler

Freestanding and Countertop



Features and benefits



Better water backed by science.

- Patented Firewall® UVC technology deactivates up to 99.9999% of bacteria and viruses.
- Culligan proprietary filtration reduces unwanted contaminants like lead, microplastics, and forever chemicals (total PFAS)†.
- BioCote® inhibits the growth of odor-causing bacteria and mold on components of the dispenser, reducing the potential buildup of stains and odors.



C-Sense smart monitoring technology

- 24/7 monitoring tracks water quality, filter life, and system performance, and uses cellular technology to send real-time data to the Culligan Cloud.
- Flags issues early and tells our experts exactly what needs attention, minimizing service disruptions.
- Shuts off automatically in the event of a leak or if water quality drops below our standards, so you never get less than the best.




Modern design and hydration experience.

- Simple touchscreen makes it easier to choose between six water modes: cold, ambient, light sparkling, extra sparkling, hot and extra hot.
- Engineered for fast installation, seamless maintenance, and a footprint that fits where you need it.
- Premium materials like glass panel and metal drip tray elevate the design and reflect the quality of what's inside.




Enjoy bottled water taste without the waste.

- Meet your sustainability goals by using your existing water supply. No deliveries, no plastic waste, just better water on demand.
- Track your impact with a real-time display that shows you how many single-use 500 ml plastic bottles you've avoided.
- Create less waste by replacing only the inside of the filter, unlike standard filters that require discarding the entire cartridge.



†Filtration performance may vary depending on the type of filter or filtration system combination selected. *Volume of water below 12°C, based on ambient and inlet water temperatures of 21°C. **Up to 99.9999% bacteria, up to 99.99% viruses, up to 99.9% cysts

Dark Grey




Light Grey






Dimensions

Freestanding



Countertop



Water options

Ambient	Cold	Hot	Extra Hot	Light Sparkling	Extra Sparkling

Specifications and performance

	Freestanding	Countertop
Colour Options	1. Dark Grey 2. Light Grey	1. Dark Grey 2. Light Grey
Dimensions (min-max)	320mm/12.6" (W) x 490mm/19.29" (D)* x 1259.5mm/49.59" (H) *Including Dispense head 320mm/12.6" (W) x 540.5mm/21.28" (D)** x 1259.5mm/49.59" (H) **Including Drip tray	380mm/14.96" (W) x 510mm/20.08" (D)* x 440mm/17.32" (H) *Including Dispense head 380mm/14.96" (W) x 518mm/20.39" (D)** x 440mm/17.32" (H) **Including Drip tray
Weight (Net)	34.6kg	29.8kg
Dispensing area height	303 mm/12"	264 mm/9.69"
Display	Touchscreen with multilingual user interface	
Drip tray capacity	800 ml / 27.05 oz	660 ml/22.31 oz
Cooling (dispensing) capacity	23.5 l/h* (*volume of water below 12°C, based on ambient and inlet water temperatures of 21°C)	19 l/h* (*volume of water below 12°C, based on ambient and inlet water temperatures of 21°C)
Number of 200 ml chilled glasses/h	117.5	95
Heating (dispensing) capacity	8.5 l/h* (*volume of water up to 87°C, based on ambient and inlet water temperatures of 21°C)	
Number of 200 ml hot cups/h	41	
Water tanks capacity	N/A - Ice bath technology (cold); 1.5 L (hot)	
Flow rate	2.0 LPM	
Min/Max operating temperature	2°C–32°C	
Min/max water temperature	Adjustable: Cold: minimum 2°C (factory set at 5°C); Hot: maximum 93°C (factory set at 87° C).	
Refrigerant gas	R600a	
Noise level	35db	
Operating pressure	0.5-3bar	
Max electrical consumption	1058W	

Technology

Water Purification system	Firewall® UVC technology: Certified by IAPMO R&T to NSF/ANSI 55 Class A, NSF P231 Protocol for Microbiological Water Purifiers, US EPA Guide Standard, NSF/ANSI 372 for lead free compliance and CSA B483.1.
Firewall UV lamp	13W with UV performance monitoring
Filters included	1. Advanced Wrapped Carbon: 1µm pleated Wrap + 5µm CBC filter. Certified to NSF 42 for Chlorine and Particulate Class I, and NSF 401 for Microplastics particles. (provided as standard) 2. High Performance Carbon: 1µm CBC filter. Certified NSF 42 for Chlorine and Particulate Class I, NSF 53 for Cyst, Lead, Asbestos, Total PFAS, Turbidity, NSF 401 for Microplastics particles. (optional add-on)
Filtration options (depending on incoming water conditions and desired water filtration output)	1. Anti-scale Filter: (for Hot water system only) Polyphosphate filters contain slow soluble polyphosphate beads with the ability to diminish the scale build-up in hot tanks. (optional add-on) 2. Taste improving Remineralisation CB filter: The added minerals enhance the flavor and mouth feel, or a more natural and pleasant water taste. (optional add-on)

Installation requirements

Voltage (EMEA)	220~240V/50Hz/60Hz
Compressor	85W/50Hz, 100W/60Hz with R600a refrigerant
Water connection	¼" push fit inlet
Ventilation space	50 mm from rear

Culligan™

Culligan UK
culligan.co.uk
0333 600 1845
sales.cuk@culligan.co.uk



Firewall technology is certified by IAPMO R&T to NSF/ANSI 55 Class A, NSF P231, US EPA Microbiological Guide Standard, NSF/ANSI 372 and CSA B483.1.



Culligan reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice.
Culligan and the Culligan logo are trademarks in countries where the Group operates.